




A CSW Industrials Company

TECHNICAL DATA

MetaFlex® Pro

Floor Expansion Joint Fire Barrier - 2 Hour
07 95 00



PRODUCT DESCRIPTION

High performance single package, drop-in floor fire barrier.

IDEAL FOR

- Applications where a fire rated floor cover is required

ADVANTAGES

- Single drop-in package provides full 2 hour rating
- Rigid flanges hold barrier in place during installation
- Factory fabricated male and female ends for quick splicing
- No caulk required at joint edges

LIMITATIONS

- Provided in 10'-0" (3048mm) maximum lengths

RELATED PRODUCTS

- MetaFlex® Pro Floor Fire Barrier - 3 Hour
- MetaFlex® Pro Shear Floor Fire Barrier
- MetaFlex® Pro Undermount Floor Fire Barrier

PERFORMANCE

Joint Sizes

8" - 36" (203mm - 914mm) Maximum Opening

Movement Capabilities:

Permits unrestrained movement of the joint without disengagement of the fire barrier.

Expansion/contraction

Vertical shear
 Contact factory for details

Per ASTM E1399

Meets IBC 715.3 fire test criteria for fire-resistant joint system

Meets IBC 715.6 requirements for fire-resistant joint systems in smoke partitions and smoke barriers

2 hour fire resistance ratings per UL 2079 & ASTM E1966

<2 SCFM/LF Air Leakage L-Rating per UL 2079

Meets CAN/ULC-S115 standards for fire resistant joint systems.

METAFLEX® PRO FLOOR EXPANSION JOINT FIRE BARRIER

ADDITIONAL DOCUMENTATION

- Product details
- Installation instructions
- ASTM E1399
- Warranty
- SDS documentation
- LEED documentation

WARRANTY

Standard Warranty: 5 years

Sample warranty available upon request